



TYPE	Max. Number of conductors & Type	A Thread	B Wrench size	C Tail Length Zero Halogen	D Cable Length	E Cable Dia	F	G Dia	H	I
HPS-17-1-5	5 (CS013)	1/2 NPT	7/8			0.45	2.02	1.00	2.35	1.06
HPS-16-1-8	8 (CS013)	3/4 NPT	1 1/16			0.45	4.06	1.23	3.00	1.57
HPS-15-1-19	19 (CS018)	1 NPT	1 3/8			0.75	4.34	1.60	3.42	1.87
HPS-14-1-30	30 (CS354)	1 1/4 NPT	1 3/4			0.81	4.56	2.05	3.45	1.86

Standard Specifications:

Part numbering: HPS-SIZE –X-conductors, X=1 is a right angle penetrator, X=2 is a straight entry penetrator. Include inboard “C” and outboard “D” cable lengths.

Body material: Aluminum-silicone-bronze, polyurethane.

Leak-proof shear notch.

Conductor Voltage rating: 500 Vrms.

Minimum insulation resistance: 100 M-ohms minimum at 1,000v test voltage.

Depth rating: 1,490 feet / 455 meters.

Approval certificate Agency: DNV (\$300 lot charge per order), Lloyds and ABS at additional cost.